

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




D

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 7/12		A2	(11) International Publication Number: WO 99/51029 (43) International Publication Date: 7 October 1999 (07.10.99)
(21) International Application Number: PCT/IB99/00486 (22) International Filing Date: 22 March 1999 (22.03.99) (30) Priority Data: 98201034.0 1 April 1998 (01.04.98) EP (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE). (72) Inventors: MEIJERS, Patrick, F., P.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DIJKSTRA, Hendrik; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: HOEKSTRA, Jelle; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			(81) Designated States: CN, JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published Without international search report and to be republished upon receipt of that report.

(54) Title: A METHOD AND DEVICE FOR GENERATING DISPLAY FRAMES FROM A SEQUENCE OF SOURCE FRAMES THROUGH SYNTHESIZING ONE OR MORE INTERMEDIATE FRAMES EXCLUSIVELY FROM AN IMMEDIATELY PRECEDING SOURCE FRAME



(57) Abstract

For raising a frame rate, first a sequence of source frames is received at a source frame rate. For a pair of immediately adjacent source frames of this sequence, one or more intermediate frames are synthesized through a geometrical transform. In particular, each intermediate frame is based exclusively on an immediately preceding source frame. Display frames are selected from the sequence of the intermediate frames, and as the case may be, also from the source frames.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

A method and device for generating display frames from a sequence of source frames through synthesizing one or more intermediate frames exclusively from an immediately preceding source frame.

BACKGROUND OF THE INVENTION

The invention relates to a method as recited in the preamble of Claim 1. US 4,736,248 discloses how to generate display frames by interpolating between source frame pairs. The transformation algorithm is derived from point pairs that occur in both of two successive source frames. The interpolation uses the same transformation for other pixel pairs that occur in both of these source frames. Sometimes a particular source pixel is present in only one of the two source frames, so that only for that particular source pixel extrapolation must be effected. The reference intends to improve picture rendering in dynamic aerial survey.

A different field of use pertains to highly interactive computer games and similar multimedia environment types. Here, it is important to have a high frame rate, so that displayed motion will be as smooth as possible. In principle this will also allow minimal latency between user-initiated events and visual feedback connected therewith. Such is especially important for navigation control, like in flight simulation games. It has been suggested to raise the frame rate to a value comparable to the display refresh rate that may be 60-72 Hz. It has furthermore been found that Virtual Reality (VR) systems need low latency to protect a user person against motion sickness. However, the general use of interpolating according to the reference will introduce additional latency, because the various interpolation parameters will only be known after reception of the later source frame, even if among all of the pixels, certain display frame pixels will only depend on past source frame pixels.

SUMMARY TO THE INVENTION

In consequence, amongst other things, it is an object of the present invention to avoid the latency increase caused by overall interpolation. Now therefore, according to one of its aspects, the invention is characterized according to the characterizing part of Claim 1. The Z-buffer is generated during the rendering of the source frames that is not part of the invention. The Z-buffer may be used to convert the 2-D-frames into 3-D space, so that changes in perspective as well as arbitrary 3-D camera rotations and translations may be implemented (Eq.8). These two transform types are the main causes for

the changing of a scene.

A specific problem caused by extrapolating is that a scene part which was obscured in an earlier source frame may subsequently be **uncovered** in an extrapolated frame, because the obscuring object has moved in a transverse manner with respect to the obscured part. A solution is attained through lateral extrapolation from adjacent pixels that had not been subject to obscuring in the preceding source frame. The extrapolation may go along with or counter to the scanning direction. If the extrapolating operates on a background pattern or another entity with coarse granularity, the result is usually true or nearly true. On the other hand, the effect of a small item that would suddenly be uncovered from behind an obscuring object, will be ignored until arrival of the next source frame. Usually, the effect of this faking is allowable. Contrariwise to the above, restricting the extrapolation to a 2D-affine transform would often create unreasonable distortions in the extrapolated frames, because a hitherto obscuring but moved part would now be extended a great deal. This problem is solved by making the extrapolation specifically dependent on the depth (zv2) expressed in the view coordinates of Eq. 12.

A display sequence may consist of the source frames together with intermediate frames. Alternatively, all or certain source frames may be left unused provided that the intermediate frames occur often enough. The inventive technology keeps display frame latency small. On the other hand, interpolating display frames may often increase latency to an unwanted extent.

The invention also relates to a frame-based device arranged for practising the recited method. Further advantageous aspects of the invention are recited in dependent Claims.

The invention allows to calculate pixel displacements for producing intermediate frames between the frames generated by the 3-D rendering pipeline itself. The displacements may be calculated incrementally during scan conversion of the source frames, through consistently using results attained for an immediately adjacent pixel along the scan line. This requires for each next pixel only a low number of arithmetical calculations on the basis of pixels treated earlier.

The invention allows to use known camera motion with respect to a most recent source frame for producing instantaneous coherence between pixels of this source frame and pixels of an immediately following synthesized display frame according to Eq. 9.

BRIEF DESCRIPTION OF THE DRAWINGS

These and further aspects and advantages of the invention will be discussed more in detail hereinafter with reference to the disclosure of preferred embodiments, and in particular with reference to the appended Figures that show:

- 5 Figures 1A-1C, three display frame producing methods;
 Figure 2, a perspective overview of the generating;
 Figure 3, relations between device and view coordinates;
 Figure 4, the same as seen in perspective;
 Figure 5, a device for implementing the invention;
10 Table 1 gives various mathematical expressions.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Figure 1A shows a first method for raising the display frame rate. The top row has a time-sequence of uniformly spaced source frames "a". Between each pair of contiguous source frames an extra frame "b" is interpolated, as indicated by arrows. By using as display frames both the original a frames as well as the interpolated b frames, the rate is doubled. The latency is appreciable, because a b frame cannot be generated before the next a frame will have become available.

Figure 1B shows a second method for raising the display frame rate. Between each pair of contiguous source frames an extra frame "c" is extrapolated being based exclusively on the last preceding a frame, which has been indicated by arrows. To use as display frames both the original a frames and the interpolated c frames will double the rate. Latency is less than in Figure 1A, because a c frame may be generated immediately when the preceding a frame has become available.

25 Figure 1C shows a third method for raising the display frame rate. Between each pair of immediately contiguous source frames an extra frame "d" is extrapolated exclusively based on the last preceding a frame, as indicated by arrows. In contradistinction to Figure 1B, the delay between a source frame and its extrapolated d frame is nonuniform. Using half of the original a frames as well as the interpolated d frames will raise the rate by a factor of 50%. Latency is less than in Figure 1A, because a d frame may be generated immediately when the preceding a frame has become available.

Figure 2 shows a perspective overview of the generating environment as based on an XYZ-coordinate system. Actual camera position is in the origin with the axis of

view in the negative Z-direction; the camera has an "up"-direction along the positive Y-axis.

Figure 3 shows geometrical relations between device and view coordinates. The camera is again in the ORigin with its axis in the negative Z-direction. The horizontal axis in the Figure is the X_{view} -axis, the Y_{view} -axis is perpendicular to the plane of the drawing. The object OBJ has been shown projected for display on the screen at x-coordinate x_s . As shown, the Figure has a perspective or central projection. Parallel projection is a feasible alternative.

Figure 4 shows this geometry in three-dimensional space. Far at left is the eye point of the camera position. The far clipping plane fcp at right and the near clipping plane ncp in the centre are perpendicular to the viewing axis, and together delimitate a viewing angle frustum. Similar clipping planes extend in the x- and y-directions. In the projection plane the signed distances top, bottom, left and right have been indicated. Further, the distances near and far between the origin and the projection plane and the object plane have been indicated. Also the height angle θ_i has been shown.

Figure 5 shows a device for implementing the invention. The set-up is centred around communication bus 20 and main memory 30. The information to be processed is fetched from memory and sent to processing modules 22, 24, 26 that are connected in series to symbolize successive operations as will be listed in the tables hereinafter. The processing modules may be collectively mapped on shared hardware such as a CPU. After processing and possibly transient storage, the successive display frames attain subsystem 34 for display to a user. Overall control subsystem 28 is connected to the processing modules via control lines 23, 25, 27, that may lead via bus 20. In this manner, the data may in the CPU be translated into an image. Control subsystem 28 may receive control and data signals from various sources, such as manual or other inputs 32 from an actual user, external signals from other users in an interactive environment, or from cameras or further subsystems not shown for brevity.

MATHEMATICAL FORMULATION OF THE PROCEDURES

Generally, due to camera rotating, translating or zooming, the complete frame content may change with time. If the geometrical relations between the previous camera position and direction and the new camera position and direction are known, the coherence between the pixels of the old source frame and the new intermediate display frame to be extrapolated will also be known. Table 1 gives various mathematical expressions,

including relations between various coordinates, such as view space coordinates, projection coordinates, normalized device coordinates and screen-space coordinates.

First, equation (1) is the perspective projection matrix. It defines the various quantities near, far, top, bottom, left and right plane positions of the viewing frustrum shown in Figure 4. Equations (2) define a Symmetrical Viewing Frustrum; an unsymmetrical frustrum may be used as well. Next, equations (3) define the use of the height angle θ and aspect ratio a to further specify the viewing frustrum. Equation (4) expresses the relations between the projection coordinates (postscripted p) and homogeneous view coordinates (postscripted v) via the projection matrix P . Other projections such as orthogonal are also feasible. Equation (5) gives normalized device coordinates (subscripted n). Finally, equation (6) gives the screen coordinates (postscripted s). Straightforward insertion derives the ultimate relations between screen coordinates and view coordinates as given in (7). Using $\{xv1, yv1, zv1\}$ and $\{xs1, ys1\}$ as the coordinates in the source frame, then $\{xv1, yv1\}$ can be written according to equation (8).

Matrix transformation of the view coordinates due to camera motion and/or object changes is given in (9). Equation (10) gives the coordinates in the extrapolated frame, so that the expressions for $(xs2, ys2)$ can be straightforwardly found as given in (11). Further, (12) is the expression for $zv2$. Now, fz is linearly related to the screen coordinates $xs1$ and $ys1$, and fz may be incrementally computed during scan conversion by adding a constant δ that is the time derivative of the movement. Hence calculating zv requires the following:

- add δ to fz
- multiply by $zv1$
- add to $m23$

Further, $xs2$ and $ys2$ can be written according to expression (13). Also, fx and fy are linearly related to the screen coordinates $xs1$ and $ys1$, so that they may also be incrementally computed by adding a constant δ . Therefore, the incremental calculation of $xs2$ and $ys2$ requires the following, in addition to calculating $zx2$:

- calculate $zv2$ reciprocal (i.e. divide 1 by $zv2$)
- add δ to fx and add δ to fy
- multiply both these results by $zv1$
- add the two products to $h*k*m03/2$ and $h*k*m13/2$ respectively
- multiply both results by reciprocal $zv2$

- add to $w/2$ and $h/2$, respectively.

The above adds up to eight additions, five multiplications and one division.

Furthermore, many game applications will present one or more objects on the screen, which may observe a dynamic behaviour that is independent from camera movement. This behaviour may be represented by a relative transform with respect to the camera for each such object that will usually be represented as one rigid body, or as a composite made up of various interconnected rigid bodies. Object movement can be realized by multiplying the camera transformation matrix M_{cam} by the rigid-body transformation M_{obj} for all pixels of the object in question. Thereupon, the displacement functions described earlier will calculate the motion vectors of the various pixels. Each pixel should have an identifier of the object to which it belongs, which identification should furthermore point to the final transformation matrix $M = M_{cam} \cdot M_{obj}$ of that object in the view-space of the most recently rendered source frame. This can be effected by introducing an extra description plane which contains object or matrix pointers. Usually the number of such rigid bodies in any scene will be less than 256, so one extra byte per pixel should be sufficient. The object plane can be efficiently compressed with runlength encoding RLE as usually the plane will contain large areas of uniform-valued pixels that belong to a single rigid body.

TABLE 1

Define view coordinaes xv, yv, zv (0)

Projection Matrix:

$$P = \begin{bmatrix} \frac{n2}{r-1} & 0 & \frac{1+r}{r-1} & 0 \\ 0 & \frac{2n}{t-b} & \frac{b+t}{t-b} & 0 \\ 0 & 0 & -\frac{f+n}{f-n} & -\frac{2fn}{f-n} \\ 0 & 0 & -1 & 0 \end{bmatrix}; \quad (1)$$

Symetrical Viewing Frustrum given by:

$$b = -t;$$

$$l = -r \quad (2)$$

Use Height Angle ϕ and aspect ratio a to specify frustrum: $k = 1/\tan[2\phi]$.

$$a = w/h;$$

$$t = n/k; \quad (3)$$

$$r = ta;$$

Projection Coordinates:

$$\{x_p, y_p, z_p, w_p\} = P \cdot \{x_v, y_v, z_v, 1\}; \quad (4)$$

Normalised Device Coordinates:

$$\{x_n, y_n\} = \{x_p, y_p\} / w_p; \quad (5)$$

Screen Coordinates:

$$\{x_s, y_s\} = \left\{ \frac{1}{2} w (x_n + 1), \frac{1}{2} h (y_n + 1) \right\}; \quad (6)$$

which by substitution is equal to:

$$\left\{ \frac{w}{2} - \frac{h k x_v}{2 z_v}, \frac{h}{2} - \frac{h k y_v}{2 z_v} \right\} \quad (7)$$

So, using $\{x_v1, y_v1, z_v1\}$ and $\{x_s1, y_s1\}$ as the coordinates in the source frame, then $\{x_v1, y_v1\}$ can be written as:

$$\{x_v1, y_v1\} = \left\{ \frac{(w - 2 x_s1) z_v1}{hk}, \frac{(h - 2 y_s1) z_v1}{hk} \right\} \quad (8)$$

Matrix Transformation of the view coordinates due to camera and/or object changes:

$$M = \begin{bmatrix} m00 & m01 & m02 & m03 \\ m10 & m11 & m12 & m13 \\ m20 & m21 & m22 & m23 \\ 0 & 0 & 0 & 1 \end{bmatrix}; \quad (9)$$

Coordinates in the intermediate frame:

$$\{x_v2, y_v2, z_v2, w_v2\} = M \cdot \{x_v1, y_v1, z_v1, 1\}; \quad (10)$$

So:

$$\{x_s2, y_s2\} = \left\{ \frac{w}{2} - \frac{h k x_v2}{2 z_v2}, \frac{h}{2} - \frac{h k y_v2}{2 z_v2} \right\} = \quad (11)$$

$$\left\{ \frac{1}{2} w \left[1 - \frac{hk \left[m03 + m02 z_v1 + \frac{m00(w-2x_s1)z_v1}{hk} + \frac{m01(h-2y_s1)z_v1}{hk} \right]}{w z_v2} \right], \right. \\ \left. \frac{1}{2} h \left[1 - \frac{k \left[m13 + m12 z_v1 + \frac{m10(w-2x_s1)z_v1}{hk} + \frac{m11(h-2y_s1)z_v1}{hk} \right]}{z_v2} \right] \right\}$$

and z_v2 is equal to:

$$z_v2 = m23 + \left[m22 + \frac{m20(w-2x_s1)}{hk} + \frac{m21(h-2y_s1)}{hk} \right] z_v1 \quad (12)$$

$$= m23 + f_z z_v1$$

f_z is linearly related to the screen coordinates x_s1 and y_s1 , so that f_z can be incrementally

computed by adding a constant delta during scan conversion. Hence the incremental computation of $zv2$ requires:

- add delta to fz
- multiply by $zv1$
- add to $m23$

$xs2$ and $ys2$ can be rewritten as:

$$\left\{ \frac{w}{2} - \frac{hkm03/2 + (hkm02 + m00(w - 2xs1) + m01(h - 2ys1))zv1/2}{zv2}, \right. \\ \left. \frac{h}{2} - \frac{hkm13/2 + (hkm12 + m10(w - 2xs1) + m11(h - 2ys1))zv1/2}{zv2} \right\} \quad (13)$$

$$= \left\{ \frac{w}{2} - \frac{hkm03/2 + fxzv1}{zv2}, \frac{h}{2} - \frac{hkm13/2 + fyvz1}{zv2} \right\}$$

Also fx and fy are linearly related to the screen coordinates $xs1$ and $ys1$, such that they can be incrementally computed by adding a constant delta. So the incremental computation of $xs2$ and $ys2$ requires (additionally to the computation of $xv2$):

- calculate $zv2$ reciprocal (divide 1 by $zv2$)
- add delta to fx and add delta to fy
- multiply both results by $zv1$
- add to $h k m03/2$ and $h k m13/2$ respectively
- multiply both results by reciprocal $zv2$
- add to $w/2$ and $h/2$ respectively.

This sums up to: 1 div, 5 mults, and 8 adds!

CLAIMS:

1. A method for displaying a first sequence of display frames, comprising the steps of:
 - receiving a second sequence of source frames at a source frame rate, and synthesizing on the basis of said second sequence for a pair of immediately adjacent source frames one or more intermediate frames through using a geometrical transformation method,
 - and being characterized in that each intermediate frame is based exclusively on an immediately preceding source frame, through extrapolation from camera transformations, and through on the basis of Z-buffer information, in-frame extrapolating uncovered deeper pixels from likewise deeper but at present continually visible such deeper pixels,
 - for on the basis of a sequence of said intermediate frames, and as the case may be, also on the basis of said source frames selecting said display frames at a raised display frame rate with respect to said source frame rate.
2. A method as claimed in Claim 1, whilst using known camera motion with respect to a most recent source frame for producing instantaneous coherence between pixels of the latter source frame and pixels of an immediately following synthesized display frame.
3. A method as claimed in Claim 1, and based on in-frame extrapolation that operates exclusively along with or counter to display lines scan motion.
4. A method as claimed in Claim 1, while furthermore displaying a solid body in an extrapolated frame according to a transformation matrix $M = M_{cam} * M_{obj}$.
5. A method as claimed in Claim 1, whilst ignoring an uncovered item that relates to no continually visible pixel, until arrival of a next source frame that has such item as rendered.
6. A frame-based device arranged for displaying a first sequence of display

frames, and comprising:

receiving means for receiving a second sequence of source frames at a source frame rate, and synthesizing means for synthesizing on the basis of said second sequence for a pair of immediately adjacent source frames one or more intermediate frames through using
5 a geometrical transformation method,

characterized in that said synthesizing means are arranged for basing each intermediate frame exclusively on an immediately preceding source frame, through extrapolation from camera transformations, and through on the basis of Z-buffer information, in-frame extrapolating uncovered deeper pixels from likewise deeper but at present continu-
10 ally visible such deeper pixels,

and outputting means fed by said synthesizing means for on the basis of a sequence of said intermediate frames, and as the case may be, also on the basis of said source frames outputting said display frames at a raised display frame rate with respect to said source frame rate.

15

7. A device as claimed in Claim 6, wherein said synthesizing means are arranged for receiving camera motion information with respect to a most recent source frame for producing instantaneous coherence between pixels of the latter source frame and pixels of an immediately following synthesized display frame.

20

8. A device as claimed in Claim 6, said synthesizing means having in-frame extrapolation means that operate exclusively along with or counter to display lines scan motion.

25

9. A device as claimed in Claim 6, and having matrix multiplication means for displaying a solid body in an extrapolated frame according to a transformation matrix $M = M_{cam} * M_{obj}$.

30

10. A device as claimed in Claim 6, and having ignoring means for ignoring an uncovered item that relates to no continually visible pixel, until arrival of a next source frame that has such item as rendered.

1/2




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3

2/2




FIG. 4




FIG. 5

THIS PAGE BLANK (USPTO)

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 7/12, 5/14, 7/26		A3	(11) International Publication Number: WO 99/51029
			(43) International Publication Date: 7 October 1999 (07.10.99)
(21) International Application Number: PCT/IB99/00486		(81) Designated States: CN, JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 22 March 1999 (22.03.99)			
(30) Priority Data: 98201034.0 1 April 1998 (01.04.98) EP		Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).			
(71) Applicant (for SE only): PHILIPS AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE).		(88) Date of publication of the international search report: 16 December 1999 (16.12.99)	
(72) Inventors: MEIJERS, Patrick, F., P.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DIJKSTRA, Hendrik; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			
(74) Agent: HOEKSTRA, Jelle; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			

(54) Title: A METHOD AND DEVICE FOR GENERATING DISPLAY FRAMES FROM A SEQUENCE OF SOURCE FRAMES THROUGH SYNTHESIZING ONE OR MORE INTERMEDIATE FRAMES EXCLUSIVELY FROM AN IMMEDIATELY PRECEDING SOURCE FRAME



(57) Abstract

For raising a frame rate, first a sequence of source frames is received at a source frame rate. For a pair of immediately adjacent source frames of this sequence, one or more intermediate frames are synthesized through a geometrical transform. In particular, each intermediate frame is based exclusively on an immediately preceding source frame. Display frames are selected from the sequence of the intermediate frames, and as the case may be, also from the source frames.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 99/00486

A. CLASSIFICATION OF SUBJECT MATTER		
IPC6: H04N 7/12, H04N 5/14, H04N 7/26 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC6: H04N, G06T		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
SE,DK,FI,NO classes as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
WPIL, JAPIO		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Efficient prediction of uncovered background in interframe coding using spatial extrapolation A Kaup et al Acoustics, Speech, and Signal Processing 1994 ICASSP-94, 1994 IEEE International Conference on 19-22 April 1994 ISBM-07803-1775-0 see column 1-4 --	1-2,4-7,9-10
A	EP 0715280 A1 (SEGA ENTERPRISES, LTD), 5 June 1996 (05.06.96), claims 1-6 --	4,9
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
26 October 1999		30 -10- 1999
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86		Authorized officer Erik Veillas/MN Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 99/00486

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9629678 A1 (IDT INTERNATIONAL DIGITAL TECHNOLOGIES DEUTSCHLAND GMBH), 26 Sept 1996 (26.09.96), see page 24 \$5; page 8 - page 15 \$1; fig 6a-8 --	1-10
A	Object oriented motion and deformation estimation using composite image segmentation Delopoulos, A.N.; Constantinides, A.G. Low Bit Imge Coding, IEE Colloquium on 1995 see page 4/3 and 4/4: section "Motion compensated extrapolation" --	1-10
A	JP 4348692 A (MATSUSHITA ELECTRIC IND CO LTD), 3 December 1992 (03.12.92), see whole document -- -----	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

28/09/99

International application No.

PCT/IB 99/00486

Patent document cited in search report			Publication date	Patent family member(s)			Publication date
EP	0715280	A1	05/06/96	JP	2883737	B	19/04/99
				CN	1129482	A	21/08/96
				WO	9535555	A	28/12/95

WO	9629678	A1	26/09/96	AU	6726596	A	08/10/96
				EP	0815538	A	07/01/98
				JP	11502335	T	23/02/99
				ZA	9602306	A	27/09/96

JP	4348692	A	03/12/92	NONE			

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)